Date: 9.2.2014 **Revision Date:** 14.4.2009

IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1. 1.1. Identification of the substance or preparation **Trade Name** Softcare Carpet Protector Code Reach registration number 1.2. Use of the chemical The intended uses of the chemical Protection of carpets Standard industrial classification 812 Use categories 61 The chemical can be used by the general public \boxtimes The chemical is used by the general public only 1.3. Identification of the manufacturer, importer or other undertaking Manufacturer, importer, other undertaking Oy Soft Protector Ltd Street address Nupurintie 4 Postal code 02820 Espoo Post-office box PL 100 Postal code 02761 Espoo Telephone number +358 9 887 0430 **Telefax** +358 9 853 7302 **Email** info@softcare.fi

1.4. Emergency telephone

Y-code

Your local poisoning center

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to Regulation (EC) No1272/2008; Flammable liquids (Category 2), Eye irritation (Category 2), Specific target organ toxicity - single exposure (Category 3)

0834157-1

According to European Directive 67/548/EEC as amended; Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.

2.2 Label elements

Pictogram

Signal word





H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
P210	Keep away from heat/sparks/open fla

Danger

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Date: 9.2.2014 Revision date: 14.4.2009

Highly flammable

Χi Irritant

R11 Highly flammable. Irritating to eyes. **R36**

R67 Vapours may cause drowsiness and dizziness.

S 7 Keep container tightly closed. S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

2.3 Other hazards - none

COMPOSITION/INFORMATION ON INGREDIENTS 3.

nazardous	s ingrealents	į
CAC No.	EC No	Ī

nazardous ingredients				
CAS-No., EC-No.,	Ingredient	Concentration	Classification	
Index-No.				
67-63-0	Isopropyl alcohol	> 96 %	Flam. Liq. 2; Eye Irrit. 2; STOT SE 3; H225, H319, H336	
603-117-00-0			F, Xi, R11 - R36 - R67	
123-86-4	n-butyl acetate	< 3 %	Flam. Liq. 3; STOT SE 3; H226, H336	
607-025-00-1			F, R10 - R66 - R67	
not available	fluoropolymer	< 1 %	Eye Irrit. 2; H319, Xi, R36	

FIRST AID MEASURES 4.

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing give artificial respiration Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eve contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

FIRE-FIGHTING MEASURES 5.

5.1. Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

5.2. Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

5.3. **Further information**

ACCIDENTAL RELEASE MEASURES 6.

6.1. Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2. **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up 6.3.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

HANDLING AND STORAGE

Precautions for safe handling

Date: 9.2.2014 **Revision date:** 14.4.2009

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

7.2. Conditions for safe storage

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Hygroscopic.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Exposure limit values

HTP-values

Isopropyl alcohol HTP-value 8 h, 200 ppm, 500 mg/m³

HTP-value 15 min, 250 ppm, 620 mg/m³

n-butyl acetate HTP-value 8 h, 150 ppm, 720 mg/m³

HTP-value 15 min, 200 ppm, 960 mg/m³

DNEL PNEC

8.2. Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Handle with gloves.

Eye protection

Face shield and safety glasses

Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. General information

Explosion limits Lower explosion limit 2 % (V), upper 12,7 % (V)

Vapour pressure 4,32 kPa (20,0 ℃), 5,87 kPa (25,0 ℃)

Density 830 kg/m^3 SolubilityWater solublePartition coefficient: n-octanol/waterlog Pow: 0,05Ignition temperature $425 \text{ }^{\circ}\text{C}$

9.2. Other information

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Conditions to avoid

Heat, flames and sparks.

Materials to avoid

Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Date: 9.2.2014 **Revision date:** 14.4.2009

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Isopropyl alcohol: LD_{50} (Oral - rat) > 4400 mg/kg

 LD_{50} (Dermal - rabbit) > 12800 mg/kg

Skin corrosion/irritation

Skin - rabbit - Mild skin irritation

Serious eye damage/eye irritation

Eyes - rabbit - Eye irritation - 24 h

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification. IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

Reproductive toxicity

no data available

Specific target organ toxicity - single exposure

May cause damage to organs.

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.

Ingestion May be harmful if swallowed.

Skin May be harmful if absorbed through skin. May cause skin irritation.

Eyes Causes eye irritation.

Signs and Symptoms of Exposure

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects.

Additional Information RTECS: NT8050000

12. ECOLOGICAL INFORMATION

Toxicity

Toxicity to fish C_{50} (Pimephales promelas, fathead minnow, 96h) 9640 mg/l Toxicity to aquatic invertebrates C_{50} (Daphnia magna, water flea, 24h) 5102 mg/l C_{50} (Desmodesmus subspicatus, green algae, 72h) C_{50} (Desmodesmus subspicatus, green algae, 72h)

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

Product

Date: 9.2.2014 **Revision date:** 14.4.2009

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packagingDispose of as unused product.

14. TRANSPORT INFORMATION

14.1. ADR/RID

UN-number: 1219 Class: 3 Packing group: II

Proper shipping name: ISOPROPANOL

14.2. IMDG

UN-number: 1219 Class: 3 Packing group: II Marine pollutant: No

Proper shipping name: ISOPROPANOL

14.3. IATA

UN-number: 1219 Class: 3 Packing group: II

Proper shipping name: ISOPROPANOL

15. REGULATORY INFORMATION

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

16. OTHER INFORMATION

Text of H-code(s) and R-phrase(s)

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

STOT SE Specific target organ toxicity - single exposure

F Highly flammable

Xi Irritant
R10 Flammable
R11 Highly flammable.
R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Further information

The above information is believed to be correct but not all inclusive and shall be used only as a guide. The information in this document is based on the present state of knowledge and is applicable to the product with regard to appropriate safety precautions.