**Date:** 9.2.2014 Revision Date: 14.4.2009

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

# 1.1. Identification of the substance or preparation

**Trade Name** 

Softcare Furniture Protector

Code

Reach registration number

#### 1.2. Use of the chemical

#### The intended uses of the chemical

Protection of fabric

Standard industrial classification 812
Use categories 61
The chemical can be used by the general public 

The chemical is used by the general public only □

# 1.3. Identification of the manufacturer, importer or other undertaking

Manufacturer, importer, other undertaking

Oy Soft Protector Ltd

Nupurintie 4

 Postal code
 02820 Espoo

 Post-office box
 PL 100

 Postal code
 02761 Espoo

 Telephone number
 +358 9 887 0430

 Telefax
 +358 9 853 7302

 Email
 info@softcare.fi

 Y-code
 0834157-1

# 1.4. Emergency telephone

Street address

Your local poisoning center

## 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

According to Regulation (EC) No1272/2008; Flammable liquids (Category 2), Eye irritation (Category 2), Specific target organ toxicity - single exposure (Category 3)

According to European Directive 67/548/EEC as amended; Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.

#### 2.2 Label elements

Pictogram

Signal word





H225 H319 H336	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.

Danger

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

**Date:** 9.2.2014 **Revision date:** 14.4.2009

contact lenses, if present and easy to do. Continue rinsing.

F Highly flammable

Xi Irritant

R11 Highly flammable. R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

S 7 Keep container tightly closed. S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### 2.3 Other hazards – none

3. COMPOSITION/INFORMATION ON INGREDIENTS				
Hazardous ingredients				
CAS-No., EC-No.,	Ingredient	Concentration	Classification	
Index-No.				
67-63-0 603-117-00-0	Isopropyl alcohol	> 96 %	Flam. Liq. 2; Eye Irrit. 2; STOT SE 3; H225, H319, H336 F, Xi, R11 - R36 - R67	
123-86-4 607-025-00-1	n-butyl acetate	< 3 %	Flam. Liq. 3; STOT SE 3; H226, H336 F, R10 - R66 - R67	
not available	fluoropolymer	< 1 %	Eye Irrit. 2; H319, Xi, R36	

## 4. FIRST AID MEASURES

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing give artificial respiration Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

# In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

## 5. FIRE-FIGHTING MEASURES

# 5.1. Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

#### 5.2. Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

### 5.3. Further information

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

# 6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### 6.3. Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

**Date:** 9.2.2014 **Revision date:** 14.4.2009

## 7. HANDLING AND STORAGE

# 7.1. Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

#### 7.2. Conditions for safe storage

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Hygroscopic.

# EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Exposure limit values

8.

**HTP-values** 

Isopropyl alcohol HTP-value 8 h, 200 ppm, 500 mg/m<sup>3</sup>

HTP-value 15 min, 250 ppm, 620 mg/m<sup>3</sup>

n-butyl acetate HTP-value 8 h, 150 ppm, 720 mg/m<sup>3</sup>

HTP-value 15 min, 200 ppm, 960 mg/m<sup>3</sup>

DNEL PNEC

## 8.2. Personal protective equipment

### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Handle with gloves.

## Eye protection

Face shield and safety glasses

#### Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

# **Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. General information

Explosion limits

Lower explosion limit 2 % (V), upper 12,7 % (V)

**Vapour pressure** 4,32 kPa (20,0 ℃), 5,87 kPa (25,0 ℃)

Density $830 \text{ kg/m}^3$ SolubilityWater solublePartition coefficient: n-octanol/water $\log \text{ Pow: } 0.05$ Ignition temperature $425 \text{ }^{\circ}\text{C}$ 

## 9.2. Other information

# 10. STABILITY AND REACTIVITY

# Chemical stability

Stable under recommended storage conditions.

### Conditions to avoid

Heat, flames and sparks.

### Materials to avoid

Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids

**Date:** 9.2.2014 **Revision date:** 14.4.2009

### Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

## 11. TOXICOLOGICAL INFORMATION

### **Acute toxicity**

Isopropyl alcohol:  $LD_{50}$  (Oral - rat) > 4400 mg/kg

 $LD_{50}$  (Dermal - rabbit) > 12800 mg/kg

#### Skin corrosion/irritation

Skin - rabbit - Mild skin irritation

# Serious eye damage/eye irritation

Eyes - rabbit - Eye irritation - 24 h

# Respiratory or skin sensitization

no data available

# Germ cell mutagenicity

no data available

# Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification. IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

# Reproductive toxicity

no data available

## Specific target organ toxicity - single exposure

May cause damage to organs.

## Specific target organ toxicity - repeated exposure

no data available

#### **Aspiration hazard**

no data available

# Potential health effects

**Inhalation** May be harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.

Ingestion May be harmful if swallowed.

**Skin** May be harmful if absorbed through skin. May cause skin irritation.

Eyes Causes eye irritation.

### Signs and Symptoms of Exposure

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects.

Additional Information RTECS: NT8050000

# 12. ECOLOGICAL INFORMATION

### **Toxicity**

Toxicity to fish  $LC_{50}$  (Pimephales promelas, fathead minnow, 96h) 9640 mg/l Toxicity to aquatic invertebrates  $EC_{50}$  (Daphnia magna, water flea, 24h) 5102 mg/l  $EC_{50}$  (Desmodesmus subspicatus, green algae, 72h) > 2000 mg/l

# Persistence and degradability

no data available

## Bioaccumulative potential

no data available

# Mobility in soil

no data available

## PBT and vPvB assessment

no data available

## Other adverse effects

no data available

## 13. DISPOSAL CONSIDERATIONS

#### **Product**

**Date:** 9.2.2014 **Revision date:** 14.4.2009

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

# Contaminated packaging

Dispose of as unused product.

# 14. TRANSPORT INFORMATION

#### 14.1. ADR/RID

UN-number: 1219 Class: 3 Packing group: II

Proper shipping name: ISOPROPANOL

### 14.2. IMDG

UN-number: 1219 Class: 3 Packing group: II Marine pollutant: No

Proper shipping name: ISOPROPANOL

#### 14.3. IATA

UN-number: 1219 Class: 3 Packing group: II

Proper shipping name: ISOPROPANOL

## 15. REGULATORY INFORMATION

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

## 16. OTHER INFORMATION

# Text of H-code(s) and R-phrase(s)

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

STOT SE Specific target organ toxicity - single exposure

F Highly flammable

Xi Irritant
R10 Flammable
R11 Highly flammable.
R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

#### **Further information**

The above information is believed to be correct but not all inclusive and shall be used only as a guide. The information in this document is based on the present state of knowledge and is applicable to the product with regard to appropriate safety precautions.